

RUBITREK A/T

VERSITILE ALL-TERRAIN TRACTION



The **RUBITREK A/T** is ready for adventure, any time and in any weather. The new Falken RUBITREK A/T provides a balance of aggressive off-road ability and rugged terrain driving along with an exceptional ride on the pavement. The optimized tread design combined with a silica tread compound provide long lasting wear along with performance in rain and snow. Designed for severe snow conditions, every tire is qualified by the Rubber Manufacturers Association for the Three Peak Mountain Snow Flake (3PMSF) symbol. The RUBITREK A/T is packed with technology including Falken's patented 3D Canyon Sipes and an all-new proprietary lower sidewall. Full-depth sipes and grooves maintain consistent performance and appearance throughout the life of the tire.

AVAILABLE TIRE SIZES
43 SIZES

AVAILABLE RIM SIZING
15" – 20"

SPEED RATING
R • S • T

LIMITED TREAD LIFE WARRANTY
55,000 MILES / 89,000 km

RATING
SEVERE SNOW
CONDITIONS 

RIDE GUARANTEE
30 DAYS

PERFORMANCE RATINGS*



*This tire is designed for severe snow conditions and meets the RMA (Rubber Manufacturers Association) snow traction performance requirements.
† Performance ratings are based on a scale of 1 to 5 with 5 being best.
‡ Ratings are in comparison to other Falken Tires products in the same category.

TIRE SIZES

Wheel Dia.	Size	Load Range	Load Index / Speed Rating	Item Number	Measuring Rim Width (in)	Approved Rim Width Range (in)	Overall Diameter (in)	Section Width (in)	Revolutions Per Mile	Tread Width (in)	Tread Depth (mm)	Tread Depth (/32")	Tire Weight (lbs)	Max PSI (Cold)	Max Load (lbs)	U.T.Q.G.
15"	235/75R15	XL	109T	28074096	6.5	6.0 - 8.0	28.9	9.1	732	7.2	10.9	14	35	50	2271	600-A-B
	30x9.5R15LT	C/6	104S	28070127	7.5	6.5 - 8.5	29.5	9.5	708	7.3	13.6	17	44	50	1985	-
	31x10.5R15LT	C/6	109S	28070241	8.5	7.0 - 9.0	30.5	10.4	685	8.2	14.1	18	50	50	2270	-
	32x11.5R15LT	C/6	113R	28077702	9.0	8.0 - 10.0	31.5	11.3	664	9.0	15.1	19	56	50	2535	-
	33x12.5R15LT	C/6	108R	28077976	10.0	8.5 - 11.0	32.5	12.5	645	9.6	15.6	20	57	35	2205	-
35x12.5R15LT	C/6	113R	28077307	10.0	8.5 - 11	34.5	12.5	608	9.4	15.6	20	68	35	2535	-	
16"	235/70R16	XL	109T	28074040	7.0	6.0 - 8.0	29.0	9.4	729	7.5	10.3	13	37	50	2271	600-A-B
	245/75R16	XL	112T	28074264	7.0	6.5 - 8.0	30.5	9.8	694	7.5	10.3	13	39	50	2469	600-A-B
	255/70R16	XL	115T	28074771	7.5	6.5 - 8.5	30.1	10.2	703	8.3	10.3	13	39	50	2679	600-A-B
	265/70R16	SL	112T	28074121	8.0	7.0 - 9.0	30.6	10.8	692	8.7	10.8	14	42	51	2469	600-A-B
	265/75R16	SL	116T	28074558	7.5	7.0 - 9.0	31.7	10.6	671	8.1	10.8	14	44	51	2756	600-A-B
	LT225/75R16	E/10	115/112S	28070511	6.0	6.0 - 7.0	29.3	8.5	711	6.9	13.1	17	40	80	2680	-
	LT235/85R16	E/10	120/116S	28070986	6.5	6.0 - 7.5	31.7	9.1	658	7.0	13.6	17	48	80	3042	-
	LT245/75R16	E/10	120/116S	28070756	7.0	6.5 - 8.0	30.5	9.5	684	7.5	13.6	17	49	80	3042	-
	LT265/75R16	E/10	123/120S	28070353	7.5	7.0 - 8.0	31.7	10.4	660	8.1	14.1	18	55	80	3415	-
LT285/75R16	E/10	126/123R	28077374	8.0	7.5 - 9.0	32.8	11.1	637	8.8	14.6	18	60	80	3750	-	
LT305/70R16	E/10	124/121R	28077564	9.0	8.0 - 9.5	32.8	12.1	637	9.7	15.1	19	64	65	3525	-	
LT315/75R16	E/10	127/124R	28077988	8.5	8.0 - 11.0	34.6	12.3	606	9.6	15.6	20	74	65	3860	-	
17"	235/75R17	SL	109T	28074089	6.5	6.0 - 8.0	31.1	9.1	679	7.2	10.9	14	38	51	2271	600-A-B
	245/65R17	SL	111T	28074166	7.0	7.0 - 8.5	29.5	9.7	719	8.1	10.3	13	39	50	2403	600-A-B
	245/70R17	XL	114T	28074677	7.0	6.5 - 8.0	30.6	9.8	691	8.0	10.3	13	40	50	2601	600-A-B
	255/70R17	SL	112T	28074891	7.5	6.5 - 8.5	31.1	10.2	679	8.3	10.3	13	43	51	2469	600-A-B
	265/65R17	XL	116T	28074776	8.0	7.5 - 9.5	30.6	10.6	697	8.8	10.3	13	42	50	2756	600-A-B
	265/70R17	SL	115T	28074576	8.0	7.0 - 9.0	31.7	10.8	668	8.7	10.8	14	47	51	2679	600-A-B
	285/70R17	SL	117T	28074640	8.5	7.5 - 9.5	32.8	11.3	647	9.2	10.8	14	51	51	2833	600-A-B
	LT235/80R17	E/10	120/117R	28077546	6.5	6.0 - 7.5	31.8	9.1	655	6.9	13.6	17	49	80	3085	-
	LT245/75R17	E/10	121/118S	28070776	7.0	6.5 - 7.5	31.7	9.5	657	7.5	13.6	17	51	80	3195	-
LT265/70R17	E/10	121/118S	28070339	8.0	7.0 - 8.5	31.9	10.7	653	8.7	14.1	18	53	80	3195	-	
LT285/70R17	E/10	121/118S	28070394	8.5	7.5 - 9.0	33.0	11.6	632	9.3	14.6	18	59	80	3195	-	
LT315/70R17	E/10	121/118S	28070963	9.5	8.0 - 11.0	34.6	12.7	604	10.0	15.6	20	73	65	3195	-	
18"	255/70R18	SL	113T	28074284	7.5	6.5 - 8.5	32.1	10.2	658	8.3	10.3	13	45	51	2535	600-A-B
	265/60R18	XL	114T	28074805	8.0	7.5 - 9.5	30.6	10.5	694	8.5	10.3	13	43	50	2601	600-A-B
	265/65R18	SL	114T	28074033	8.0	7.5 - 9.5	31.5	10.6	675	8.8	10.3	13	46	51	2601	600-A-B
	265/70R18	SL	116T	28074757	8.0	7.0 - 9.0	32.6	10.8	646	8.7	10.8	14	47	51	2756	600-A-B
	275/65R18	SL	116T	28074460	8.0	7.5 - 9.5	32.1	10.9	663	9.1	10.8	14	47	51	2756	600-A-B
	LT275/65R18	E/10	123/120S	28070568	8.0	7.5 - 9.0	32.1	10.7	651	9.1	14.6	18	60	80	3415	-
LT275/70R18	E/10	125/122S	28070381	8.0	7.0 - 8.5	33.4	11.0	624	9.0	14.6	18	61	80	3640	-	
20"	275/55R20	XL	117T	28074522	8.5	7.5 - 9.5	31.9	11.1	661	8.9	10.3	13	48	50	2833	600-A-B
	275/60R20	SL	115T	28074060	8.0	7.5 - 9.5	33.1	10.8	640	8.9	10.3	13	46	51	2679	600-A-B
	LT275/65R20	E/10	126/123S	28070792	8.0	7.5 - 9.5	34.1	10.6	611	9.1	14.6	18	66	80	3750	-
	LT285/55R20	E/10	122/119T	28074045	9.0	8.0 - 10.0	32.4	11.2	642	9.7	14.6	18	58	80	3305	-
	LT305/55R20	E/10	121/118S	28070202	9.5	8.5 - 11.0	33.2	12.3	626	10.4	15.1	19	71	65	3195	-
35x12.5R20LT	E/10	121R	28077262	10.0	8.5 - 11.0	34.6	12.5	603	10.6	15.6	20	76	65	3195	-	

Never mix tires of different size, construction or type on an axle except for temporary use as a spare tire. Always refer to vehicle owners manual for proper tire fitment.

No UTQG rating for LT sizes.


Product images are for illustrative purposes only. Tread design, technical information and tire construction subject to change without notice and may vary by size.

TIRE HIGHLIGHTS



HEAT DIFFUSER TECHNOLOGY

in the lower sidewall dissipates heat to protect the internal tire components. Keeping this critical area of the tire cool ensures vehicle stability even when towing or carrying heavy loads.




3D CANYON SIPE TECHNOLOGY

interlocks the shoulders to resist wear from high torque as well as providing additional handling stability.



RUGGED & RIGID TREAD BLOCKS

feature support ramps and step-down features that provide tread-pattern rigidity in the contact patch enhancing vehicle stability and handling, while also preventing stones from becoming trapped in the grooves.



AGGRESSIVE UPPER SIDEWALL

along with offset shoulder blocks protect the tire from sharp rocks and provide additional off-road traction at low tire pressures or in off-camber situations.



DEEPEST TREAD IN THE CATEGORY¹

provides long lasting wear as well as consistent snow and hydroplane resistance throughout the life of the tire.

¹ LT Sizes, 20/32nds inches.



SILICA TREAD COMPOUND²

delivers superior wear life and wet performance.

² non-LT sizes.

TECHNOLOGY



OUTER APEX SIDEWALL

features a secondary bead apex that acts as a heat shield to protect the internal casing of the tire, resulting in confident handling and durability with the added benefit of sidewall protection on rough roads and trails.

RUBITREK A/T

VERSITILE ALL-TERRAIN TRACTION

POPULAR FITMENTS*

- | | |
|---------------------|----------------|
| CHEVROLET COLORADO | NISSAN TITAN |
| CHEVROLET SILVERADO | RAM TRUCKS |
| FORD F-SERIES | TOYOTA 4RUNNER |
| JEEP CHEROKEE | TOYOTA TACOMA |
| NISSAN FRONTIER | TOYOTA TUNDRA |

* Top-ranking examples based on third-party data.

